
SV24

Fune per gru a torre - autogru - paranchi - *Steel wire rope for tower cranes - mobile telescopic cranes - crane*



Diametro *Diameter* *mm*	*Peso* *Weight* *Kg/m*	*Carico di rottura minimo garantito* *Minimum breaking load guaranteed* *1960 N/mm²* *kN*	 *2160 N/mm²* *kN*
8	0,28	47,3	52
9	0,36	61	67
10	0,44	72,5	82
11	0,54	87,7	100
12	0,65	104	120
13	0,76	122	141
14	0,87	148	161
16	1,14	193	212

- Eccellenti performance nella resistenza alla fatica
- Ideale per sollevamenti di media ed elevata altezza
- Particolarmente adatta per macchine che richiedono avvolgimenti multi strato ed alto grado di flessibilità

SV 24
COSTRUZIONE: fune antigirevole con trefoli esterni tondi 24x7 - 28x7
RESISTENZA: 1960 N/mm^2 - 2160 N/mm^2
AVVOLGIMENTO: parallelo destro o sinistro
FINITURA: zincata lubrificata

- Excellent fatigue resistance
- Ideal for hoisting of medium to high height
- Particularly suitable for machines that require multi-layer windings and a high degree of flexibility

SV 24
CONSTRUCTION: non-rotating rope with external round strands of 24x7 to 28x7
TENSILE GRADE: 1960 N/mm^2 - 2160 N/mm^2
LAY: right-hand or left-hand lang's lay
FINISH: galvanized lubricated